

Federzuordnungstabelle Typ EURO DST 9 bis April 2001

BRM Höhe (mm)	1.800	2.000	2.250	2.375	2.500	2.625	2.750	3.000	3.250	3.500	3.750	4.000	4.250	4.500	4.750	5.000	BRM Höhe (mm)								
3.125	16	22	24	30	30	30	36	36	DST-Euo doppelwandig								3.125								
3.000	16	22	21	30	30	30	36	40									40	45	3.000						
2.875	16	15	21	30	30	30	36	35									39	39	44	2.875					
2.750	16	15	21	30	30	30	29	35									39	39	44	48	2.750				
2.625	10	15	21	30	30	30	29	29									35	34	38	38	43	2.625			
2.500	10	15	21	20	20	20	29	28									35	34	38	38	43	43	47	47	2.500
2.375	10	15	14	20	20	20	29	28									28	34	33	38	37	42	42	46	2.375
2.250	10	15	14	14	14	13	19	28									27	34	33	37	37	42	42	41	2.250
2.125	4	9	14	13	13	13	20	19									28	27	27	33	32	37	42	42	2.125
2.000	4	9	14	13	13	13	19	19									18	23	27	26	32	32	42	42	2.000
1.875	4	3	8	13	13	13	19	18	18	23	26	26	32	31	31	41	1.875								
1.725	3	3	8	13	13	13	19	18	23	23	26	32	32	31	31	41	1.725								
BRM Höhe (mm)	1.800	2.000	2.250	2.375	2.500	2.625	2.750	3.000	3.250	3.500	3.750	4.000	4.250	4.500	4.750	5.000	BRM Höhe (mm)								
BRM Breite (mm)																									

